



**numen**  
INVERTER

**SURPRISE MOMENTS**

Inverter Split Wall Mounted  
**PRODUCT CATALOGUE**  
2025

# AI ECOMASTER

## Master AI Saving, Better Comfort Cooling

Real AI master control based on giga-scale big data, Balancing energy-saving and comfort needs.



Master Giga Data



Master Precise Control



Master Comfort Saving



## 1 Bigger Than Bigger, Master Giga Data

Powered by the industry's largest operational data, ECOMASTER can deliver much faster and more accurate comfort energy saving, far ahead of conventional inverter technologies.


### Master World's Largest Inverter AC Production

# 41 Million



### Master Industry Largest AC Operational Data

# 100 Billion Level Data



### Master Energy Innovation Globally with

# 805 Patents



## 2 Smart Than Smarter, Master Precise Control

By pre-training the multi-dimensional environmental factors, ECOMASTER can predict the best AC operation way based on user historical preferences and dynamic room conditions.

### AI ECOMASTER

#### Faster and Precise Control Achieving Energy Saving and Comfort

- Multi-dimensional Data Sources Real-time indoor and ambient condition data, AC operational data, weather forecast data
- Predict data every 30s and response to the environment temperature precisely.



### Other ECO

#### Imprecise Control, High Temperature Fluctuation, Energy Wastes

- Single data source of only indoor temperature
- Simple control logic from limited preset settings without reacting to changes in the condition of the room

## 3 Inverter Than Inverter, Master Comfort Saving



# 38%\*

LESS ENERGY


Percentage energy saving compare to the lowest 2 stars rating air conditioning. 38% is applicable to 1HP Numen Inverter.

MASTER  
**30%\* Extra**  
Energy Saving with AI Algorithm

MASTER AI Temperature Control

# ±0.3°C

Verified by



\* Compare the 4-hour power consumption of the same model in ECOMASTER mode and normal mode.

# Prime Guard

## Built to Last

Prime technologies in reliability and durability Guard comfort cool.



## TU1 Corrosion-Resistance Copper Tube

**70%** less impurities than ordinary tubes.

Compared with the ordinary tubes, TU1 reduces the impurity content, and its corrosion resistance and thermal conductivity are improved.

**TP2**

More Impurities & Less Consistency

**VS**

**TU1**

Fewer Impurities & Better Consistency




## Silver Shield Anti-corrosive Coating

Both sides of the evaporator are coated with "environmentally friendly polymer coating & technological baking method" to prevent the copper pipe from being polluted and corroded by air pollutants, making it more secure and durable.

**<0.1%** vs **>50%**

Anti-corrosive Coated Pipe

Ordinary Pipe



Verified by **intertek** Depended on the using industrial environment with salt contamination (Ref. ISO 21207: 2015, Annex A, test method B)

## Wide Voltage Operation

Thanks to Ultra Electronic Control System, Midea's Inverter can work stably in 80V-265V\*. Whether it is the peak of urban electricity consumption or the shortage of power supply in remote areas, it can always work consistently and smoothly.

CONVENTIONAL 184V 265V

**MIDEA 80V 265V**



\* The voltage operation range of BP3 is 80-265V, BP2 is 150-265V, and 18k and above is 120-256V.

## Reliable PCB with UV Conformal Coating


Curing using UV light, Greener and with 2x Thicker and Higher Density Protection

Corrosion Area **<0.02%\*** Rating Number **9.8\*\***

Verified by **intertek**

\* Depended on the using industrial environment with salt contamination (Ref. ISO 21207: 2015, Annex A, test method B, JIS Z 2371:2015 Annex JC)


\*\* The full rating number is 10.



## HYPER GRAPFINS™

**12.5X\*** Corrosion Resistance than Blue Coated Fins

Graphene is a single monolayer of carbon atoms, tightly bound in a hexagonal honeycomb lattice. When graphene is added to the anti-corrosion layer, the density of the layer can be improved to resist corrosion.



\* The judgment standard of corrosion resistance is based on comparing the maximum corrosion area ratio of the rating number in JIS Z 2371-2015. Compared samples are Midea fins: Midea blue coated fins in HD2202-2/HW3308. Midea HYPER GRAPFINS in HMD01/HW3308.

## AUTO DEDUSTING



When the AC is turned off, the fan blade of the outdoor unit will automatically rotate in reverse to get rid of the accumulated sand and dust, ensuring the AC is clean and operates well in any environment.


# Healthy Air Management

## I - Clean Reclean the AC, Refresh your breath.

Midea Inverter AC has been upgraded from water washing (20 mins) to frost cleaning (42 mins), which can remove more dust and bacteria, keeping the AC clean and performing well.

<b>1</b> <b>Condensed Water</b> 10min 	<b>2</b> <b>Frosting</b> 10min 	<b>3</b> <b>Washing</b> 20min 	<b>4</b> <b>Drying</b> 2min 	 <b>Total</b> <b>42mins</b>
Cooling mode & Mid-speed wind	The temperature cools rapidly ( $T \leq -10^{\circ}\text{C}$ ) and frost forms on the evaporator surface.	Defrost into water to remove dust and dirt.	Dry the evaporator to prevent mold growth.	

**99%**  
VIRUS ELIMINATION



**ION GENERATOR**

Tested by Guangdong Detection Center of Microbiology. Test time: 2h. Virus: H1N1.

## Air Magic 365 Days to a Clean, Fresh, Healthy Air

Under the effect of electric field generated by ion generator, millions of positive and negative ions are formed to eradicate bacteria and viruses with higher sterilization rate. Moreover, running the "Air Magic" feature in fan mode 24 hours a day consumes less than 1 kWh.

## Cool Flash

The latest generation of COOLFLASH achieves faster cooling speed, stronger air circulation, larger swing angle, and further airflow distance through dual upgrades of hardware and software. With one press of the COOLFLASH button, the room can be quickly cooled down to the desired temperature, immersing you in an evenly cool room.

\* Tested by Midea Lab for 10-minute cooling. The room temp of 1.5HP Numen AC dropped by 5°C, with an initial room temp is 36°C, and the outdoor temp is 43°C, 60% RH.  
\*\* Tested on the 1.5HP Numen AC in Coolflash mode by Midea Lab, the farthest distance refers to a wind speed of no less than 0.3m/s

**5°C** in 10 mins\*  
from 36°C to 31°C

Air Volume **665M<sup>3</sup>/h** | Air Distance\*\* **8.1M**

**Cool Flash**



## Power Cooling Beats the Heat

Even at high temperatures of up to **55°C**, Midea Inverter still operates effectively, beating heat and providing optimal cooling to the room.



## Smart Control (optional)

**Smart Home** Smart Compatible

**LBS**  
Location Based Services



The AC can adjust its mode based on the location, e.g. automatically turning on the AC from 15km away before arriving home.

**Sleep Curve**



Customize your preferred sleep mode with sleep duration, temperature and fan speed.

**Energy Management**



Enjoy a life of visible energy saving

## Gear Control

Upgraded from 3 levels (50%, 75%, 100%) to 5 levels (20%, 40%, 60%, 80%, 100%), more levels enable more accurate power control to meet different usage scenarios. When you feel cool enough, you can choose a lower power level to save energy.






## Easy To Install

### Pull-down Structure

Just loosen ONE screw to remove the PULL-DOWN Structure, and stretch out the Built-in Support Holder for enlarged working space and improved visibility, providing installers with a better installation solution.

- 1** Screw  
■ Just Loosen
- 2** 204mm  
■ Enlarged Working Space
- 3** Built-in Support Holder and Groove  
■ More Convenient & Stable



### Easier, Quicker & More Installer-friendly Solution

#### IN Embedded Pipe

##### Enlarged Working Space & Improved Visibility

Loosen 1 screw to dismantle the pull-down frame for higher working efficiency



Previous AC



Insufficient Working Space resulting in having to loosen 5 screws and dismantle the entire frame

#### IN 5cm Ceiling

A better solution without disassembling the entire frame




Previous AC



Limited ceiling space makes it difficult for AC to recover the frame.

## Installer-friendly Design



**Mounting Plate Upgrade**  
Easier to align the mounting location



**Two Opening Angles of Panel**  
Available at 85° and 60°, suitable for more installation scenarios



**Pocket Hole**  
More space for a wrench



**Wire Tunnel**  
Tool-less Wiring  
Fewer steps, Easier Wiring

Previous AC



Cutter Required

# Easy To Maintain

Quick and Easy to Pull-out PCB The Easier Solution for PCB Replacement

**5 steps**

Maintenance efficiency increased by **32%**  74S



**1** 3S  
Open the Front Panel



**2** 5S  
Remove ONE screw from the Electronic Control Box



**3** 3S  
Take Away the Electronic Control Box Cover



**4** 60S  
Remove Wire Terminals



**5** 3S  
Pull Out the PCB

**Ordinary AC**

**8 steps**  109S



**1** 3S  
Open the Front Panel



**2** 15S  
Remove Screws from the Frame



**3** 15S  
Unlock 3 Buckles/Slider Locks



**4** 15S  
Remove the Front Frame



**5** 5S  
Remove Screws from the Electronic Control Box



**6** 3S  
Take Away the Electronic Control Box Cover



**7** 60S  
Remove Wire Terminals



**8** 3S  
Pull Out the PCB

Pull-out Fan Motor The Easier Solution for Fan Motor Replacement

**4 steps**

Maintenance efficiency increased by **72%**  3min 20s



**1** 1min  
Remove the Front Frame



**2** 1min  
Remove the Electronic Control Box



**3** 1min  
Take Away the Motor Bracket



**4** 20S  
Pull Out the Fan Motor

**Previous AC**

**7 steps**  12min



**1** 3S  
Turn On the AC



**2** 2min  
Recycle Refrigerant




**3** 5min  
Remove the IDU from the Wall



**4** 1min  
Remove the Front Frame



**5** 1min  
Remove the Electronic Control Box




**6** 2min  
Remove the Evaporator



**7** 1min  
Pull Out the Fan Motor

# Easy To Clean

The more accessible the wind wheel is, the deeper the cleaning.



# FEATURES




# APPEARANCE



# SPECIFICATIONS

Model	Indoor		MSNE-10CRFN8-ID	MSNE-13CRFN8-ID	MSNE-19CRFN8-ID	MSNE-25CRFN8-ID
	Outdoor		MSNE-10CRFN8-OD	MSNE-13CRFN8-OD	MSNE-19CRFN8-OD	MSNE-25CRFN8-OD
Cooling Capacity	Rated (Min-Max)	Btu/h	10,000 (1,250-11,109)	12,000 (3,900-13,000)	18,000 (6,900-18,500)	24,000 (9,600-25,500)
Power consumption	Rated (Min-Max)	W	890(135-1,080)	1,134(150-1,300)	1,758(190-1,850)	2,512(790-2,750)
Running current	Rated (Min-Max)	A	3.87(1.01-4.7)	4.78(1.6-5.65)	7.64(1.48-8.7)	10.92(3.95-11.95)
CSPF(Cooling seasonal performance factor)		Wh/Wh	4.99	5.32	5.30	4.95
Energy Efficiency Star Rating						
Power supply	V,Hz,Ph		220-240V-,50Hz,1Ph (power supply to indoor)			
Indoor unit	Indoor air flow (H)	m <sup>3</sup> /h(cfm)	630 (370)	630 (370)	895 (526)	1,112(654)
	Indoor Sound level (H/M/L)	dB(A)	39.5/34.5/31.5	39.5/34.5/31.5	44.5/37/34.5	47/40/36.5
	Dimension(W*D*H)	mm	825x199x286	825x199x286	986x216x305	1059x230x328
	Packing (W*D*H)	mm	895x290x365	895x290x365	1065x300x385	1140x420x330
	Net/Gross weight	Kg	7.8/9.8	7.8/9.8	10.1/13.9	12.1/16.6
Outdoor unit	Outdoor Sound level	dB(A)	52	55	56	59
	Dimension(W*D*H)	mm	668x252x469	720x270x495	765x303x555	805x330x554
	Packing (W*D*H)	mm	765x270x515	835x300x540	887x337x610	915x370x615
	Net/Gross weight	Kg	17/18.6	18.9/20.8	24.2/26.9	29.9/32.5
	Refrigerant Charge	g	R32/360g	R32/400g	R32/650g	R32/830g
	Design pressure	MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ6.35/Φ9.52(1/4"/3/8")	Φ6.35/Φ9.52(1/4"/3/8")	Φ6.35/Φ12.7(1/4"/1/2")	Φ6.35/Φ12.7(1/4"/1/2")
	Max. refrigerant pipe length	m	25	25	30	50
	Max. difference in level	m	10	10	20	25
Indoor-Outdoor connection wiring (Not included)			4x1.5 mm <sup>2</sup>	4x1.5 mm <sup>2</sup>	4x2.5 mm <sup>2</sup>	4x2.5 mm <sup>2</sup>
Power supply wiring (Not included)			3x1.5 mm <sup>2</sup>	3x1.5 mm <sup>2</sup>	3x2.5 mm <sup>2</sup>	3x2.5 mm <sup>2</sup>
Thermostat type			Wireless Remote Control (Smart control, Wired control optional)			


# INDOOR UNIT DIMENSION



NUMEN INDOOR DIMENSION			
Model	W (mm)	D(mm)	H(mm)
<b>MSNE-10CRFN8</b>	825	199	286
<b>MSNE-13CRFN8</b>	825	199	286
<b>MSNE-19CRFN8</b>	986	216	305
<b>MSNE-25CRFN8</b>	1059	230	328





# OUTDOOR UNIT DIMENSION

MSNE-10CRFN8-OD








# OUTDOOR UNIT DIMENSION

MSNE-13CRFN8-OD







# OUTDOOR UNIT DIMENSION

MSNE-19CRFN8-OD




# OUTDOOR UNIT DIMENSION

MSNE-25CRFN8-OD



DETAIL A  
SCALE 1:1



# ERROR CODE QUICK TROUBLESHOOTING

Display Code	Error Information	Quick Solution
dF	Defrost	Normal Display, not error code
CL	Active Clean	
nF	Filter replacement reminder(power on display for 15 seconds)	
FC	Forced cooling	
AP	AP mode of WIFI connection	
CP	Remote switched off	
SD	Power abnormal detection	Check power supply
EH 00/EHOR	Indoor EEPROM malfunction	Check power and Indoor PCB
EL 01	Communication malfunction between indoor and outdoor units	S signal wire coneniton, outdoor main control board, indoor PCB
EH 02	Zero-crossing signal detection error	Check connection wire, check indoor PCB
EH 03	The indoor fan speed is operating outside of the normal range	Check indoor fan motor wire connection,indoor PCB, indoor Fan motor
EC 51	Outdoor EEPROM parameter error	Outdoor main PCB
EC 52	Condenser coil temperature sensor T3 is in open circuit or short circuit	Check outdoor condenser coil sensor or main PCB
EC 53	Outdoor ambient temperature sensor T4 is in open circuit or short circuit	Check outdoor condenser room temp. sensor or main PCB
EC 54	Compressor discharge temperature sensor TP is in open circuit or short circuit	Check outdoor compressor discharge temp. sensor or main PCB
EH 60	Indoor room temperature sensor T1 is in open circuit or short circuit	Check indoor room temp. sensor
EH 61	Evaporator coil middle temperature sensor T2 is in open circuit or short circuit	Check indoor coil temp. sensor
EC 07	The outdoor fan speed is operating outside of the normal range	Check outdoor fan motor wire connection,outdoor main PCB, outdoor Fan motor
EH 0b	Communication error between indoor PCB and display PCB	Check indoor display board connection wire
EL 0C	Refrigerant leakage detection System lacks refrigerant	Check gas leaking, copper pipe flare nut, indoor PCB
PC 00	IPM malfunction or IGBT over-strong current protection	Wire connection, Inverter modular, Outdoor Main PCB, compressor
PC 01	Outdoor unit voltage protection (low or high voltage)	Power supply, Inverter modular, Outdoor Main PCB, Reactor
PC 02	"Compressor top discharge temperature sensor protection IPM module or High pressure protection"	Check sensor, gas pressure, system blockage
PC 04	Inverter compressor drive error	Inverter modular, Outdoor Main PCB, compressor
PC 40	Communication error between outdoor main chip and compressor driven chip	Check outdoor main PCB
PC 03	High pressure protection or low pressure protection	Check outdoor main PCB
PC 08	Current overload protection	Wire connection, Outdoor Main PCB, Reactor, Outdoor Fan motor
FH 0P	AP mode is active but there is no WIFI kit installed	Check Wi-Fi connection

## Midea Scott & English Electronics Sdn Bhd (194517-X)

No. 16, Jalan Chan Sow Lin, 55200 Kuala Lumpur Fax: 03-9221 7204 / 03-9221 1434 / 03-9221 3509

### PENANG

No. 35, Jalan Perniagaan Gemilang 1,  
Pusat Perniagaan Gemilang,  
14000 Bukit Mertajam, Pulau Pinang.  
Tel: 04-548 3938 Fax: 04-548 9698

### JOHOR

No. 25, Jalan Seri Impian 1,  
Taman Impian Emas,  
81300 Skudai, Johor.  
Tel: 07-562 4898 Fax: 07-557 7898

### PERAK

No. 38, Persiaran Perindustrian Pengkalan 10,  
Kawasan Perindustrian Pengkalan,  
31500 Lahat, Perak.  
Tel: 05-323 2529 Fax: 05-323 2529

### PAHANG

No. 258, Ground Floor, Jalan Air Putih,  
Taman Air Putih Mewah,  
25350 Kuantan, Pahang Darul Makmur.  
Tel: 09-560 6668 Fax: 09-09-560 5050

### MALACCA

No. 385-L, Taman Peringgit Jaya,  
75400 Peringgit, Melaka.  
Tel: 06-292 1940 Fax: 06-286 7107

### KOTA BHARU

PT 1436, Ground Floor,  
Taman Koperatif, Tanjung Chat,  
15300 Kota Bharu, Kelantan.  
Tel/Fax: 09-743 1202

### SABAH

Inanam Suria Commercial Centre,  
Lot B, Unit 0-9, Unit 1-9,  
Ground Floor and First Floor,  
88450, Kota Kinabalu, Sabah.  
Tel: 088-421 428 Fax: 088-431 427

### SARAWAK

1st Floor, Lot 8517,  
Stutong Commercial Centre, Jalan Stutong,  
93350 Kuching, Sarawak.  
Tel: 082-363 167 Fax: 082-366 167

Midea Care Line

**1300-22-0133**

Dealer's Stamp:



midea\_malaysia



Midea Malaysia



midea.com/my